



PRODUCT SPECIFICATION

(產品規格書)

產品名稱 Description	產品料號 Part No.	圖號 Drawing No.	
8975WP Series USB 3.1 C Type Receptable Right Angle Solder+SMD Type Waterproof IPX7	8975WP-C24C00RDB13NT	S3220220301-03	
PRODUCT NAME (產品名稱)	DOCUMENT No.: (文件編號)	Rev. (版本)	OUPIIN (歐品) Prepared (製作) 2022.07.06
8975WP Series USB 3.1 C Type Receptable Right Angle Solder+SMD Type Waterproof IPX7 (RoHS)	Q8975-PSS-002	A (I654)	
	Approved (核准)	Checked (審核)	
	Q.A. Section Chief	Ruru Chen	



PRODUCT SPECIFICATION OF OUPIIN

1. SCOPE 範圍

This product specification defines the product performance and the test methods to ascertain the performance of the 8975WP Series USB 3.1 C Type Receptable Right Angle Solder+SMD Type Waterproof IPX7, which is designed and manufactured by Oupiin Electronic Co.,Ltd. This product specification is applicable but not only for those part numbers which be shown in the cover page.

本產品規格書規定了由歐品電子有限公司生產的 8975WP Series USB 3.1 C Type Receptable Right Angle Solder+SMD Type Waterproof IPX7 型連接器，產品的特性及測試方法。本產品規格書適用於但不局限於封面所顯示的產品料號。

2. REFERENCE DOCUMENTS 參考文件

MIL-STD-202 Test method for electrical components 電子零件測試方法
EIA364 Test method for electrical components 電子零件測試方法

3. FEATURE & DIMENSIONS 特徵及尺寸

3.1. PRODUCT DIMENSION 產品尺寸

These connectors shall have the dimensions as shown in drawing.

本產品的相關尺寸參考圖面。

3.2. PCB/PANEL LAYOUT 印刷電路板佈局

The recommended PCB layout is shown in drawing.

本產品適用的 PCB layout 參考圖面。

3.3. BILL OF MATERIAL 材料清單

Harmful material control follow the requirement of RoHS. The bill of material and product number is described in drawing.

有害物質控制符合RoHS指令要求，本產品使用的材料參見圖面。

3.4. MECHANICAL & ELECTRICAL CHARACTERISTIC 機械及電氣特性

The connector shall have the mechanical and electrical performance as described in drawing.

本產品的機械及電氣特性見圖面

3.5. PACKAGING 包裝

Products shall be packaged according to requirements specified in purchase order for safe delivery, connector container and the packaging method are shown in package specification.

產品可依客戶指定要求包裝，包裝材料與包裝方式參見產品包裝規範



PRODUCT SPECIFICATION OF OUPIIN

3.6. RATING CURRENT AND RATING VOLTAGE 額定電流與額定電壓

Rating current is 3A, rating voltage is 20VAC RMS

額定電流3A，額定電壓20VAC RMS

3.7. STORAGE AND OPERATING TEMPERATURE 儲存與使用溫度

Operating Temperature : -40°C~+80°C.

Storage Temperature : -30°C~+60°C.

操作溫度：-40°C~+80°C.

儲存溫度：-30°C~+60°C.

4. PERFORMANCE AND TEST DESCRIPTION 性能及測試

4.1. REQUIREMENT 要求

Product is designed to meet electrical, mechanical, and environmental performance requirements specified in Table I.

本產品設計符合附表一所述的機械，電氣及環境要求。

4.2. TEST CONDITION 測試條件

Unless otherwise specified, all tests shall be performed at ambient environmental conditions.

除非特別註明，所有測試在室溫條件下完成。

4.3. SAMPLE SELECTION 樣品選擇

Test samples shall be selected at random from current production. No test samples shall be reused.

Samples are pre-conditioned with 10cycles of durability. Each group shall be containing 5 test samples.

測試樣品從現生產的產品中隨機抽取，所有測試過的樣品不得重複使用。樣品已預先插拔10次，每組測試有5個樣品。



PRODUCT SPECIFICATION OF OUPIIN

Table I: Test Requirements and Procedures

附表一:測試要求與方法

Items (項目)	Requirements (要求)	Test Methods (檢測方法)
1. Confirmation of Product (產品確認)	Product shall be conforming to the requirements of applicable product drawing. 產品必須滿足相關檔的規定	Visually, dimensions and functionally inspected per applicable product drawing. 依相關產品圖面，檢查產品的外觀、尺寸及功能
2. Contact Resistance (接觸阻抗)	Initial : 40 mΩ Max	Subject mated contacts assembled in housing to closed circuit of 100 mA max. 20 mV max. Per EIA-364-23 所述固定在外殼裡的端子連結到一個封閉回路中測試，電流 100 mA max，電壓 20 mV max。 適用：EIA-364-23
3. Insulation Resistance (絕緣阻抗)	100 MΩ Min. 最小 100 MΩ	Measure by applying 100VDC between the adjacent contacts. Per EIA-364-21 測試產品在相鄰的端子間施加電壓 100VDC。 適用：EIA-364-21
4. Dielectric Withstanding Voltage (耐電壓)	Without damages such as arc or breakdown etc. 產品無損壞現象，例如：電弧，擊穿等等	Connector must withstand test potential of 100 VAC for 1 minute, current leakage must be 0.5mA Max. Per EIA-364-20 產品必須承受測試電壓 100 VAC，時間 1 分鐘，漏電流不大 0.5mA。 適用：EIA-364-20.
5. Mating/Un-mating Force (插入力/拔出力)	Mating force : 5~20N Un-mating force : 8~20N 插入力：5~20N 拔出力：8~20N	At a speed of 12.5 mm/minute, apply axial insert the mating part into fully or pull out from the subject product. Per EIA-364-13 以 12.5mm/分鐘的速度，軸向完全插入對配外掛程式到被測產品中或從被測產品中拔出。 適用：EIA-364-13



PRODUCT SPECIFICATION OF OUPIIN

<p>6. Durability (耐久性)</p>	<p>After testing, no physical damage. Contact Resistance: 100 mΩ Max. after testing. 測試後，產品外觀無損壞，接觸阻抗最大 100 mΩ</p>	<p>Repeat mate and unmated for connector 10000 cycles, at a speed of 200 cycles per hour. EIA-364-09 重復進行配合產品 10000 次插拔，速度每小時 200 次。 適用：EIA-364-09</p>
<p>7. Solder ability (可焊性)</p>	<p>There shall have a solder coverage of 95% minimum 產品在測試完成後，焊接部位粘錫面積大於 95%</p>	<p>Soldering time: 4±1 seconds. Temperature: 250±5°C. Per EIA-364-52 焊接時間：4±1 秒 溫度：250±5°C 適用：EIA-364-52</p>