



## PRODUCT SPECIFICATION OF OUPIIN

# PRODUCT SPECIFICATION

## (產品規格書)

### Ordering information

6111- 60 C 00 B A  
Series No. of Pin Count C: Selective Gold Plated 00:Gold Flash B: Black A: Tray Package  
06~68

PRODUCT NAME (產品名稱)	DOCUMENT No.: (文件編號)	Rev. (版本)	OUPIIN
Transition Plug 2.00mm (RoHS)	6111spec	A1	(歐品)
	Approved (核準)	Checked (審核)	Prepared (製作)
	Q.A. Section Chief	Amy Chiu	AUG.23/2012



# PRODUCT SPECIFICATION OF OUPIIN

<b>1. SCOPE (範圍)</b> .....	<b>3</b>
<b>2. REFERENCE DOCUMENTS (參考文件)</b> .....	<b>3</b>
<b>3. FEATURE &amp; DIMENSIONS (特徵及尺寸)</b> .....	<b>3</b>
3.1. <i>PRODUCT DIMENSION (產品尺寸)</i> .....	3
3.2. <i>PCB/PANEL LAYOUT (印刷電路板佈局)</i> .....	3
3.3. <i>BILL OF MATERIAL (材料清單)</i> .....	3
3.4. <i>MECHANICAL &amp; ELECTRICAL CHARACTERISTIC (機械及電器特性)</i> .....	3
3.5. <i>PACKAGING (包裝)</i> .....	3
3.6. <i>RATING CURRENT AND RATING VOLTAGE (額定電流與額定電壓)</i> .....	4
3.7. <i>STORAGE AND OPERATING TEMPERATURE (儲存與使用溫度)</i> .....	4
<b>4. Environmental (環境要求)</b> .....	<b>4</b>
4.1. <i>SOLDERABILITY (可焊性)</i> .....	4
4.2. <i>RESISTANCE TO SOLDER HEAT (耐焊接熱)</i> .....	4
WAVE SOLDERING (波峰焊) .....	4
1.Preheat (預熱) .....	4
2.Soldering (焊接) .....	4
3.Cool Down (冷卻) .....	4
<b>5. PERFORMANCE AND TEST DESCRIPTION (性能及測試)</b> .....	<b>5</b>
5.1. <i>REQUIREMENT (要求)</i> .....	5
5.2. <i>TEST CONDITION (測試條件)</i> .....	5
5.3. <i>SAMPLE SELECTION (樣品選擇)</i> .....	5
<b>Table I: Test Requirements and Procedure</b> .....	<b>6-7</b>
(附錄一: 測試要求)	
<b>Table II: Material</b> .....	<b>8-10</b>
(附錄二: 材料證明)	



# PRODUCT SPECIFICATION OF OUPIIN

## 1. SCOPE (範圍)

This product specification defines the product performance and the test methods to ascertain the performance of the Transition Plug 2.00mm, which is designed and manufactured by Oupiin Electronic Co.,Ltd.

(本產品規格書規定了由歐品電子有限公司生產的 Transition Plug 2.00mm, 型連接器,產品的特性及測試方法.)

## 2. REFERENCE DOCUMENTS (參考文件)

MIL-STD-1344A	Test method for electrical connector (電子連接器測試方法)
MIL-STD-202F	Test method for electrical components (電子零件測試方法)
EIA 364	Test method for electrical components (電子零件測試方法)

## 3. FEATURE & DIMENSIONS (特徵及尺寸)

### 3.1. PRODUCT DIMENSION (產品尺寸)

These connectors shall have the dimensions as shown in drawing.

(本產品的相關尺寸參考圖面.)

### 3.2. PCB/PANEL LAYOUT (印刷電路板佈局)

The recommended PCB layout is shown in drawing.

(本產品適用的 PCB layout 參考圖面.)

### 3.3. BILL OF MATERIAL (材料清單)

Harmful material control follow the requirement of RoHS. The bill of material and product number is described in drawing.

(有害物質控制符合RoHS指令要求.本產品使用的材料參考附件.)

### 3.4. MECHANICAL & ELECTRICAL CHARACTERISTIC (機械及電氣特性)

The connector shall have the mechanical and electrical performance as described in drawing.

(本產品的機械及電氣特性見圖面：)

### 3.5. PACKAGING (包裝)

Products shall be packaged according to requirements specified in purchase order for safe delivery.

Products required carrier tape should meet the proper specification per purchase order. Connector



## PRODUCT SPECIFICATION OF OUPIIN

container and the packaging specification is shown in package drawing.

(產品包裝可依客戶指定要求.本產品採用 Tray Packag 包裝，具體見包裝圖面.)

### 3.6 RATING CURRENT AND RATING VOLTAGE 額定電流與額定電壓

Current Rating is 1.0A, Voltage Rating is 150V DC/AC RMS.

額定電流 1.0A，額定電壓 150V DC/AC RMS。

### 3.7 STORAGE AND OPERATING TEMPERATURE 儲存與使用溫度

Temperature range: -40°C~+105°C, including terminal temperature rise for rating current.

溫度範圍：-40°C~+105°C，包含接觸端子的額定電流溫升。

## 4. ENVIRONMENTAL (環境要求)

### 4.1. SOLDERABILITY (可焊性)

Connectors meet solder ability to MIL-STD-202F. Finish shall be free of contaminants.

(產品可焊性符合 MIL-STD-202F 標準規定的相關要求，表面不得有污染物.)

### 4.2. RESISTANCE TO SOLDER HEAT (耐焊接熱)

#### WAVE SOLDERING (波峰接)

Three cycles. Each cycle consisting of three consecutive phased.

(三個週期，每個週期包括三個連續的階段完成；)

#### 1. Preheat (預熱)

Increase in temperature not to exceed 4°C per second.

(溫度增加不超過 4°C /秒,)

#### 2. Soldering (焊接)

Maximum allowable time wave soldering temperature of 150 °C is 90~120 seconds.

Temperature in this interval is 245°C, not to exceed 5 seconds.

(波峰焊溫度150°C時最長不超過90~120秒. 最高溫度245°C時間不超過5秒.)

#### 3. Cool Down (冷卻)

Cool down shall not exceed 6°C per second.

(冷卻速度不超過6°C/秒.)

#### Note: (說明)

Device temperature measurements are referenced from the top-center of the package outer surface.

(設備溫度量測時以從頂部中間位置測量為準.)



## **PRODUCT SPECIFICATION OF OUPIIN**

### **5. PERFORMANCE AND TEST DESCRIPTION**

#### **(性能及測試)**

##### **5.1. REQUIREMENT (要求)**

Product is designed to meet electrical, mechanical, and environmental performance requirements specified in **Table I**.

(本產品設計符合附表一所述的機械，電氣及環境要求。)

##### **5.2. TEST CONDITION (測試條件)**

Unless otherwise specified, all tests shall be performed at ambient environmental conditions.

(除非特別注明，所有測試在室溫條件下完成；)

##### **5.3. SAMPLE SELECTION (樣品選擇)**

Test samples shall be selected at random from current production. No test samples shall be reused. Samples are pre-conditioned with 10cycles of durability. Each group shall be containing 5 test samples.

(測試樣品從現生產的產品中隨機抽取，所有測試過的樣品不得重複使用。樣品已預先插拔10次，每組測試有5個樣品；)



## PRODUCT SPECIFICATION OF OUPIIN

**Table I: Test Requirements and Procedures**

(附錄一:測試要求)

Items (項目)	Requirements (要求)	Test Methods (檢測方法)
1. Confirmation of Product (產品確認)	Product shall be conforming to the requirements of applicable product drawing. (產品必須滿足相關檔的規定)	Check the dimensions and functions per applicable product drawing in your eyes. (目視，尺寸及功能依產品圖面檢查)
2. Contact Resistance (接觸阻抗)	15 mΩ Max. initial (最大.初態)	Subject mated contacts assembled in housing to closed circuit of 100 mA max. at open circuit voltage of 20 mV max. (所述固定在外殼裏的端子連結到一個封閉回路中測試：電流 100 mA，電壓 20 mV max.)
3. Insulation Resistance (絕緣阻抗)	1000 MΩ Min. (最小)	Measure by applying test potential between the adjacent contacts, and between the contacts and ground in the mated connector. MIL-STD-202, Method 302, Condition B (500 V DC±10%). (測試產品端子間以及端子與接地間的電阻，適用：MIL-STD-202,方法 302，條件 B )(500V DC±10%)
4. Dielectric Strength (耐電壓)	Connector must withstand test potential of 500 V AC for 1 minute. Current leakage must be 0.5 mA max. (樣品必須承受測試電壓 500V AC，時間一分鐘，漏電流不大於 0.5 mA.)	Measure by applying test potential between the adjacent contacts, and between the contacts and ground in the mated connector. MIL-STD-202, Method 301. (測試產品端子間以及端子與接地間的電壓，適用：MIL-STD-202，方法 301。)
5. Thermal shock (熱衝擊)	After testing, no damage, Contact Resistance 30 mΩ max.. Dielectric Strength should be OK, Insulation Resistance should be 1000 MΩ min. (測試後,產品無損壞，接觸阻抗：30 mΩ 最大；耐電壓測試 OK，絕緣阻抗 1000MΩ 最小;)	Temperature range from -40°C to +85°C .Start from -40°C, after 30 min. change to +85°C; change time is no more than 30 seconds. Total 5 cycles. MIL-STD-202, Method 107D, condition A. (溫度變化範圍： -40°C ~ +85°C；從 -40°C 開始，30 分鐘後換到+85°C；轉換時間不超過 30 秒；共 5 個循環.適用：MIL-STD-202，方法 107D，條件 A.)



## **PRODUCT SPECIFICATION OF OUPIIN**

<p>6.High Temperature Life (高溫老化)</p>	<p>After testing, no damage, Contact Resistance 30 mΩ max.. Dielectric Strength should be OK, Insulation Resistance should be 1000 MΩ min. (測試後,產品無損壞, 接觸阻抗: 30 mΩ 最大; 耐電壓測試 OK, 絕緣阻抗 1000MΩ 最小;)</p>	<p>Subject product to 105±3°C for 96 hours continuously. MIL-STD-202, Method 108. (產品置於 125±3°C 連續 96 小時, 適用 MIL-STD-202, 方法 108。)</p>
<p>7. Solder ability (可焊性)</p>	<p>Appearance of the specimen shall be inspected after the test with the assistance of a magnifier capable of giving a magnification of 10 X for any damage such as pinholes, void or rough surface. (樣品在測試完成後, 在放大倍數為 10 倍的顯微鏡下, 檢查外觀損壞如: 小孔, 空焊, 外觀粗糙度;)</p>	<p>Soldering time: 3 to 5 Seconds (焊接時間: 3~5 秒) Soldering Temperature: 245±5°C. (焊接溫度: 245±5°C.)</p>



## PRODUCT SPECIFICATION OF OUPIIN

Material Housing : 023-PBT (Black)

[SGS Test Report Click here](#)

[如需 SGS 測試報告請點選此處](#)

### 長春人造樹脂廠股份有限公司

台北市松江路三〇一號七樓

### CHANG CHUN PLASTICS CO., LTD.

NO.301, SONGKIANG ROAD, 7<sup>TH</sup> FL.,  
TAIPEI, 10477 TAIWAN

TEL:886-2-25001883  
FAX:886-2-25018018

#### CCP PBT 4830BK PROPERTIES

MATERIAL : PBT4830BK

VENDOR: CHANG CHUN PLASTICS CO., LTD.

TEST ITEM	TEST METHOD	UNIT	QC RANGE
比重 (SPECIFIC GRAVITY)	ASTM D-792		≥ 1.57
灰份 (ASH)		%	28-32
抗張強度 (TENSILE STRENGTH)	ASTM D-638	KG/CM <sup>2</sup>	≥ 1000
伸長率 (ELONGATION)	CCP METHOD	%	≥ 3.0
抗折強度 (FLEXURAL STRENGTH)	ASTM D-790	KG/CM <sup>2</sup>	≥ 1500
抗折模數 (MODULUS)	ASTM D-790	KG/CM <sup>2</sup>	≥ 70000
衝擊強度 (IMPACT STRENGTH, NOTCHED)	ASTM D256	KG-CM/CM	≥ 7.0
熔融指數 (MELT INDEX)	ASTM D-1238	g/10MIN	14-26





## PRODUCT SPECIFICATION OF OUPIIN

Material Housing :UL

QMFZ2 Component - Plastics Wednesday, May 25, 2005 E59481

**CHANG CHUN PLASTICS CO LTD**  
7TH FL 301 SONGKIANG RD TAIPEI TW

Material Designation: **PBT-4830**

Product Description: Polybutylene Terephthalate (PBT), glass reinforced, designated "LONGLITE" furnished as pellets.

Color	Min. Thick. (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str	IEC GWIT	IEC GWFI
ALL	3.0-3.2	V-0	0	1	75	75	75	-	-
<b>CTI: 3</b>	<b>IEC CTI (V): -</b>	<b>HVTR: 2</b>			<b>D495: 7</b>			<b>IEC Ball Pressure (°C): -</b>	

Dielectric Strength (kV/mm): -

ISO Tensile Strength (MPa): -

ISO Tensile Impact (kJ/m<sup>2</sup>): -

Volume Resistivity (10<sup>10</sup>ohm-cm): -

ISO Flexural Strength (MPa): -

ISO Inod Impact (kJ/m<sup>2</sup>): -

Dimensional Stability(%): -

ISO Heat Deflection (°C): -

ISO Charpy Impact (kJ/m<sup>2</sup>): -

Report Date: 9/1/1987

Underwriters Laboratories Inc®

UL94 small-scale test data does not pertain to building materials, furnishings and related contents. UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in components and parts of end-product devices and appliances, where the acceptability of the combination is determined by ULL.



# PRODUCT SPECIFICATION OF OUPIIN

Material Contact : Copper Alloy (Phosphor Bronze)

[SGS Test Report Click here](#)

[如需 SGS 測試報告請點選此處](#)



## REPORT OF MATERIAL TEST

DATE: FEB.23,2005

4

Customer: 歐品電子有限公司	Commodity: C 5191 R PHOSPHOR BRONZE STRIP ( H )	ISO 9002:4M8Y035-00 台正字第 3545 號
Applied Standard: CNS 9503 Phosphor Bronze Sheets, Plates and Strips		

Chemical Analysis Test										
Work No.	Size of Product			P(%)	Sn(%)	Cu+Sn+P(%)				P.O. NUMBER
	Thickness (mm)	Width (mm)	Length (mm)							
		Standard			0.030 - 0.350	5.50 - 7.00	min. 99.50			
3CC195A	0.300	305.000		0.145	6.000	99.974				

Mechanical & Physical Test										
Work No.	Size of Product			Dimension Test		Tension Test		Hardness Test HV	Grain Size (mm)	Electric Conductivity (%)
	Thickness (mm)	Width (mm)	Length (mm)	Thickness (mm)	Width (mm)	Tensile Strength (kgf/mm <sup>2</sup> )	Elongation (%)			
		Standard			-	(-) 0.10 - (+) 0.00	min. 58	-	min. 170	-
3CC195A	0.300	305.000		GOOD.	GOOD.	63.57	21.38	201.0 - 203.0	-	14.4

QC Supervisor 鄭建益

**MINCHALI METAL INDUSTRY CO., LTD.**  
 11, Pei Yuan Road, Chung Li City, Taiwan, R. O. C.  
 Tel : (03)4526141-5 (03)4526017-9