



# PRODUCT SPECIFICATION

## 產品規格書

產品名稱 Description	產品料號 Part No.	圖號 Drawing No.
2011 Series Pin Header 2.54mm Single/Double/Triple Row Straight/Right Angle Solder Type	2011-1XxxGxx(T)Sx-x	2011D01042
	2011-1XxxGxx(T)RB	2011D01003
	2011-1XxxGxx(T)LB	2011D01105
	2011-1XxxG00RW-4-4-0.4B	2011D01077
	2011-2XxxGxx(T)SB	2011D01004
	2011-2XxxGxx(T)RB	2011D01102
	2011-3XxxGxx(T)SB	2011D01005
	2011-3XxxGxx(T)RB	2011D01103

PRODUCT NAME 產品名稱	DOCUMENT No.: 文件編號	Rev. 版本	OUPIIN
2011 Series Pin Header 2.54mm Single/Double/Triple Row Straight/Right Angle Solder Type (RoHS)	Q2011-PSS-I001	F (I535)	歐品
	Approved 核准	Checked 審核	Prepared 製作
	Q.A. Section Chief	Ruru Chen	2023.11.22



# PRODUCT SPECIFICATION OF OUPIIN

## 1. SCOPE 範圍

This product specification defines the product performance and the test methods to ascertain the performance of the 2011 Series Pin Header 2.54mm Single/Double/Triple Row Straight/Right Angle Solder Type, which is designed and manufactured by Oupiin Electronic Co.,Ltd. This product specification is applicable but not only for those part numbers which be shown in the cover page.

本產品規格書規定了由歐品電子有限公司生產的 2011 Series Pin Header 2.54mm Single/Double/Triple Row Straight/Right Angle Solder 型連接器，產品的特性及測試方法。本產品規格書適用於但不局限於封面所顯示的產品料號。

## 2. REFERENCE DOCUMENTS 參考文件

MIL-STD-1344A	Test method for electrical connector	電子連接器測試方法
MIL-STD-202	Test method for electrical components	電子零件測試方法
EIA364	Test method for electrical components	電子零件測試方法

## 3. FEATURE & DIMENSIONS 特徵及尺寸

### 3.1. PRODUCT DIMENSION 產品尺寸

These connectors shall have the dimensions as shown in drawing.

本產品的相關尺寸參考圖面。

### 3.2. PCB/PANEL LAYOUT 印刷電路板佈局

The recommended PCB layout is shown in drawing.

本產品適用的 PCB layout 參考圖面。

### 3.3. BILL OF MATERIAL 材料清單

Harmful material control follow the requirement of RoHS. The bill of material and product number is described in drawing.

有害物質控制符合RoHS指令要求，本產品使用的材料參見圖面。

### 3.4. MECHANICAL & ELECTRICAL CHARACTERISTIC 機械及電氣特性

The connector shall have the mechanical and electrical performance as described in drawing.

本產品的機械及電氣特性見圖面。

### 3.5. PACKAGING 包裝

Products shall be packaged according to requirements specified in purchase order for safe delivery, connector container and the packaging method are shown in package specification.

產品可依客戶指定要求包裝，包裝材料與包裝方式參見產品包裝規範。



## PRODUCT SPECIFICATION OF OUPIIN

### 3.6. RATING CURRENT AND RATING VOLTAGE 額定電流與額定電壓

Rating current is 3A, rating voltage is 110V AC

額定電流3A，額定電壓110V AC。

### 3.7. STORAGE AND OPERATING TEMPERATURE 儲存與使用溫度

Temperature range : -40°C ~+105°C

Storage Temperature : 0°C ~+40°C, Humidity : 80%RH under. Time limit is 12 months the products are stored.

溫度範圍：-40°C ~+105°C

儲存溫度：0°C ~+40°C，濕度：80%RH 以下，產品限存時間為 12 個月。

## 4. ENVIRONMENTAL 環境要求

### 4.1. SOLDERABILITY 可焊性

Connectors meet solder-ability to EIA-364-52.and shall be free of contaminants.

產品可焊性符合 EIA-364-52. 標準規定的相關要求，表面不得有污染物。

### 4.2. RESISTANCE TO SOLDER HEAT 耐焊接熱

#### 4.2.1. WAVE SOLDER 波峰焊接

Each cycle consists of three consecutive phases. as shown in Table II.

每個焊接週期包括三個連續的階段，見附表二。

Note: 說明

Device temperature measurements are referenced from the top-center of the package outer surface.

設備溫度量測時以從頂部中間位置測量為準。

## 5. PERFORMANCE AND TEST DESCRIPTION 性能及測試

### 5.1. REQUIREMENT 要求

Product is designed to meet electrical, mechanical, and environmental performance requirements specified in Table I.

本產品設計符合附表一所述的機械，電氣及環境要求。

### 5.2. TEST CONDITION 測試條件

Unless otherwise specified, all tests shall be performed at ambient environmental conditions.

除非特別註明，所有測試在室溫條件下完成。



## *PRODUCT SPECIFICATION OF OUPIIN*

### **5.3. SAMPLE SELECTION 樣品選擇**

Test samples shall be selected at random from current production. No test samples shall be reused. Samples are pre-conditioned with 10 cycles of durability. Each group shall be containing 5 test samples at least.

測試樣品從現生產的產品中隨機抽取，所有測試過的樣品不得重複使用。樣品已預先插拔10次，每組測試至少有5個樣品。



## PRODUCT SPECIFICATION OF OUPIIN

### Table I : Test Requirements and Procedures

#### 附表一：測試要求與方法

Items 項目	Requirements 要求	Test Methods 檢測方法
1. Confirmation of Product 產品確認	Product shall be conforming to the requirements of applicable product drawing. 產品必須滿足相關檔的規定	Visually, dimensions and functionally inspected per applicable product drawing. 依相關產品圖面，檢查產品的外觀、尺寸及功能
2. Contact Resistance 接觸阻抗	20 mΩ Max. 最大 20 mΩ	Subject mated contacts assembled in housing to open circuit of 100 mA max. 20 mV max. Per EIA-364-06 所述固定在外殼裡的端子連結到一個開路回路中測試，電流 100 mA max，電壓 20 mV max 適用：EIA-364-06
3. Insulation Resistance 絕緣阻抗	1000 MΩ Min. 最小 1000 MΩ	Measure by applying test potential between the adjacent contacts, and between the contacts and ground in the mated connector. (500V DC) Per EIA-364-21 測試產品相鄰端子間以及端子與接地間的電阻 (500V DC) 適用：EIA-364-21
4. Dielectric Withstanding Voltage 耐電壓	After testing, there shall be no breakdown. 測試後，產品應無擊穿	Connector must withstand test potential of 1000V AC for 1 minute. Per EIA-364-20 產品必須承受測試電壓 1000V AC，時間 1 分鐘 適用：EIA-364-20.
5. Retention Force 保持力	0.8 Kg/pin. Min 每支最小 0.8 Kg	Apply axial pullout force the speed rate of 25.4 mm/minute. Per EIA-364-29 以 25.4 mm/分鐘的速度施加軸向拉力 適用：EIA-364-29




## PRODUCT SPECIFICATION OF OUPIIN

<p>6. Solder ability 可焊性</p>	<p>There shall have a solder coverage of 95% minimum. 產品在測試完成後，焊接部位粘錫面積大於 95%</p>	<p>Soldering time : 3 to 5 seconds. Temperature : 245±5°C Per EIA-364-52 焊接時間：3~5 秒 溫度：245±5°C 適用：EIA-364-52</p>
----------------------------------	---	--

**Table II : Weld the curve graph in crest**

附表二：波峰焊曲線圖



- |                                  |                         |
|----------------------------------|-------------------------|
| ① Preheat 80sec (1~2°C/s)        | ⑤ Dip Time 3~6sec       |
| ② $\Delta T < 150^\circ\text{C}$ | ⑥ $> 200^\circ\text{C}$ |
| ③ 235~245°C                      | ⑦ Cooling -5°C/s        |
| ④ 1~3sec                         |                         |