

# OUPIIN ENTERPRISE CO., LTD

## Moisture Sensitivity Level 'Certificate of Compliance' 濕度敏感等級符合宣告書

Most of OUPIIN products use PBT or LCP for plastic material, We declare the moisture sensitivity level(MSL) meet JEDEC J-STD-020 Level 1.

About the MSL detail information for other plastic material, Please contact with our salesperson.

The table below details the floor life time and conditions defined by J-STD-020C.

多數 OUPIIN 產品使用 PBT 及 LCP 為其塑膠材料，我方宣告其濕度敏感等級符合。

JEDEC J-STD-020 Level 1.

其他塑膠材料的 MSL 詳細資訊，請洽我方業務人員。下表的車間時間及條件定義依據 J-STD-020C 規範。

LEVEL	Floor life time	Floor condition
1	Unlimited at	$\leq 30^{\circ}\text{C}$ / 85% RH
2	1 year	$\leq 30^{\circ}\text{C}$ / 60% RH
2a	4 weeks	$\leq 30^{\circ}\text{C}$ / 60% RH
3	168 hours	$\leq 30^{\circ}\text{C}$ / 60% RH
4	72 hours	$\leq 30^{\circ}\text{C}$ / 60% RH
5	48 hours	$\leq 30^{\circ}\text{C}$ / 60% RH
5a	24 hours	$\leq 30^{\circ}\text{C}$ / 60% RH
6	Time on label	$\leq 30^{\circ}\text{C}$ / 60% RH

Declaration Certified by:  
*OUPIIN ENTERPRISE CO., LTD.*

Ruru Chen

Q. C. Section Chief

2025/3/28